

Print Base: FRITZ

The look and feel of linen with the performance & durability of polyester

Composition: 92% polyester 8% linen
Printed width: 140 cms | 55 inches
Weight: 442 g/m² | 13.04 oz/yd²
Recommended usage: Residential upholstery & drapery | Accessories & Cushions

Abrasion: 50,000 cycles
Test Standard AS 2001.2.25.2 – 2006 Martindale Method

Seam Slippage : 3.5mm length 3.0mm width
Test Standard AS 2001.2.22-2006 at 2.5N

Pilling Resistance : Rating 4-5
Test Standard IWS 1 6-1996 Martindale Method

Pilling occurs when loose fibres on the surface of a fabric tangle together and form small balls or “pills”. This should not be considered a flaw. Pilling can be minimized by vacuuming furniture regularly to remove dirt and grit. Pilling can also be removed with any de-pilling tool and will not affect the quality of the print.

CARE & MAINTENANCE

Machine washable at 30 degrees
Iron on medium heat
Tumble dry on low

Only use textile detergents
Use professional cleaners for best results



Sustainable
Green Print



SUSTAINABILITY

We strive to follow principles of sustainability through all our business activities and the entire process from weaving to production. We print locally to order and only use water-based inks and recyclable bi-products. We regularly research the latest developments in sustainable textile production to ensure we are using all available innovations to reduce the environmental impact of both our production and products.

SPOT CLEANING

Test cleaning method on hidden section first
Treat spills and stains as soon as possible:
Gently remove soil or mop any liquids from the surface of the fabric. Do not scrub. Apply dry cleaning solvent strictly according to instructions. Do not saturate the fabric with water or other cleaning liquids. If further cleaning is needed, professional use of dry-cleaning or hot water extraction machines is recommended

BLEACH CLEANING

Solution recommended 1:10

Colourfastness to light:

Test Standard ISO-BO2-1994 (Range across CMYK colours)

Colourfastness to washing:

Test Standard AS2001.4.15-2006 (Range across CMYK colours)

Colourfastness to drycleaning:

Test Standard AS2001.4.15-2006 (Range across CMYK colours)

Colourfastness to pool water:

Test Standard AS2001.4.15-2006 (Range across CMYK colours)

Colourfastness to rubbing:

Test Standard AS2687 - 1997 Class 4

Rating 5 - 6/7

Rating 5

Rating 4 - 4/5

Rating 4/5 - 5

Wet 4/5 Dry 5

